

A						
B						
C						
D						
E						
F						

mögliche Materiallösungen																						
WGR	Material																					
2R2-ZUAC54 Ø	Kegel: 1.4301(304)-2R(IIID)																					
	Platte: 2.3202 (Pb)																					
	Wetterkragen:1.4301(304)-2R(IIID)																					
2B2-ZUAC54 Ø	Kegel: 1.4301(304)-2B(IIIC)																					
	Platte: 2.3202 (Pb)																					
	Wetterkragen: 1.4301(304)-2B(IIIC)																					
2J2-ZUAC54 Ø	Kegel: 1.4301(304)-2J(GEB)																					
	Platte: 2.3202 (Pb)																					
	Wetterkragen: 1.4301(304)-2J(GEB)																					
CU-ZUAC54 Ø	Kegel:2.0090(SFCU)																					
	Platte: 2.3202 (Pb)																					
	Wetterkragen:2.0090(SFCU)																					
VZ-ZUAC54 Ø	Kegel:1.0226(DX51D)-VZ(VZ)																					
	Platte: 2.3202 (Pb)																					
	Wetterkragen:1.0226(DX51D)-VZ(VZ)																					

Ø - System-Außendurchmesser
(gilt für einwandige und doppelwandige Systeme)

Ø	60	65	80	95	100	110	115	120	125	130	140	145	150	160	165	170	175	180	185	190	195	200	
ØB	60	65	80	95	100	110	115	120	125	130	140	145	150	160	165	170	175	180	185	190	195	200	
ØC	115		140		165				190				215				240				265		
ØD	150		175		200				225				250				275				300		
E	1000																						
F	550		575		600				625				650				675				700		
kg	6,5		6,8		7,1				7,4				7,8				8,1				8,4		
Ø	205	210	215	220	225	230	235	240	245	250	255	260	265	275	280	285	290	295	300	315	320	325	
ØB	205	210	215	220	225	230	235	240	245	250	255	260	265	275	280	285	290	295	300	315	320	325	
ØC	265			290					315					340					365			390	
ØD	300			325					350					375					400			425	
E	1000																						
F	700			725					750					775					800			1000	
kg	8,4			8,7					9					9,2					9,5			11,8	
Ø	345	350	360	365	400	415	450	465	480	500	515	550	560	565	600	615	635	650	665	700	715		
ØB	345	350	360	365	400	415	450	465	480	500	515	550	560	565	600	615	635	650	665	700	715		
ØC	390		415		465		515		540		565		615		665		690		715		765		
ØD	425		450		500		550		575		600		650		700		725		750		800		
E	1005,7		1038,3		1070,90		1168,8		1201,5		1234,1		1299,3		1364,6		1397,3		1429,9		1495,1		
F	1000																						
kg	11,8		12,1		12,8		13,4		13,7		14		14,6		15,2		15,5		15,7		16,3		

notes:

DIN ISO 13920 Tolerances B

revisions-no.

A

mm / kg

date

08.03.2021

name

TRA

drawn by

checked by

approved by

modified by

Jeremias®

CHIMNEY SYSTEMS

description

Dachdurchführung 36-45° mit Bleirand und Wetterkragen

code

WGR-ZUAC54Ø

drawing-no.

01-07-04-5306-000

scale

1:14

format

A4

sheet

1 of 1